REVERSIBLE COMPACTORS

BARTELL GLOBAL

A PROVEN SERIES

IDEAL FOR LANDSCAPING

These units are perfect for any general compaction job requiring up to 12,000 lbs of compaction force. The fully hydraulic reversing mechanism sets them apart from the competition, providing flexible maneuverability for forward, backward, and spot-on compaction.

- Robust throttle control and on/off switch on handle
- Sealed belt-guards
- Standard wheel kit for built-in mobility*
- Optional extension plates*
- Straight-edge plate design
- Built-in hoist hook
- Urethane mat available to protect pavers*
- Electric start on diesel models

*not available on all models

SCAN CODE TO DOWNLOAD OUR **COMPACTION RESOURCE KIT**

BR1570

BR2750

BR3570

BR4600

BR4600

BR5100

TECHNICAL SPECS

MODEL	BR1570	BR2750	BR3570	BR4600	BR4600	BR5100
Engine Type	Honda GX160	Honda GX200	Honda GX270	Honda GX390	Yanmar L100W	
Power Output	4.8hp (3.6kW)	5.5hp (4.1kW)	8.5hp (6.3kW)	11.7hp (8.7kW)	9.3hp (6.9kW)	
Compaction Force	3461 lbf, 15 kN, 1570 kgf	6063 lbf, 27 kN, 2750 kgf	7871 lbf, 35 kN, 3570 kgf	10141 lbf, 45kN, 4600 kgf		11,244 lbf, 50kN, 5100 kgf
Max Travel Speed	65'/min (20m/min)		52'/min (16m/min)	72'/min (22m/min)		
Length	35" (88cm)	45" (114cm)	53" (134cm)	62" (157cm)		65" (161cm)
Width	14" (35cm)	17" (43cm)	18" (45cm)	19" (48cm)		20" (50cm)
Height	35" (88cm)	36" (91cm)	38" (96cm)	37" (93cm)		
Weight	193 lbs (87.5kg)	353 lbs (160kg)	529 lbs (240kg)	772 lbs (350kg)	820 lbs (372kg)	1036 lbs (470kg)
Plate Size	14" x 19" (35cm x 48cm)	17" x 28" (43cm x 70cm)	18" x 28" (45cm x 70cm)	19" x 34" (49cm x 86cm)		20" x 36" (50cm x 90cm)